

# SOUND POWERED TELEPHONE SYSTEMS

## TELEPHONES

TYPE: SCM-TA-MG

**MODEL: TA-MG-2-AU**

**(Telephone with headset connection)**

**SCM**  
SISTEMAS



### FEATURES

- Excellent speech quality.
- Single way sound-powered telephone.
- For use on open air deck areas and bridge wings.
- Material: ABS polymer (fireproof).
- Earpiece: ABS polymer (fireproof).  
Spiral cord (60 cm extensible to 1.5 m).
- Includes headset connector for noisy areas.
- Optional acoustic/luminous alarm via relay box.
- Includes metallic cableglands.

### TECHNICAL SPECIFICATIONS

Operating temperature	-20°C to +70°C
Acoustic alarm	80 dB (1m)
Relative humidity	Up to 95% (non condensing)
Assembly	Bulkhead
Weight	Approx 3 kg.
IP-rating	55
Resistive load	10A 250VAC / 30VDC
Inductive load	( $\cos\phi = 0.4$ ; L/R = 7 ms) 5A250VAC / 30VDC

# SOUND POWERED TELEPHONE SYSTEMS

## TELEPHONES

TYPE: SCM-TA-MG

**MODEL: TA-MG-2-AU**

**(Telephone with headset connection)**

**SCM**  
SISTEMAS

