

# SOUND POWERED TELEPHONE SYSTEMS

## TELEPHONES

TYPE: SCM-TA-MG

MODEL: TA-MG-3

**SCM**  
SISTEMAS



### FEATURES

- Excellent speech quality.
- 12 extensions selector switch (extending up to 24).
- For use on open air deck areas and bridge wings.
- Material: ABS polymer (fireproof).
- Earpiece: ABS polymer (fireproof).  
Spiral cord (60 cm extensible to 1.5 m).
- Optional acoustic/luminous alarm via relay box.
- Includes metallic cableglands.

### TECHNICAL SPECIFICATIONS

|                       |   |
|-----------------------|---|
| Operating temperature | -20°C to +70°C                                    |
| Acoustic alarm        | 104 dB (1m)                                       |
| Relative humidity     | Up to 95% (non condensing)                        |
| Assembly              | Bulkhead  |
| Weight                | Approx 3 kg.                                      |
| IP-rating             | 55  |
| Resistive load        | 10A 250VAC / 30VDC                                |
| Inductive load        | ( $\cos\phi = 0.4$ ; L/R = 7 ms) 5A250VAC / 30VDC |

# SOUND POWERED TELEPHONE SYSTEMS

## TELEPHONES

TYPE: SCM-TA-MG

MODEL: TA-MG-3

**SCM**  
SISTEMAS

